

AD-A128 409

INTERFACIAL TENSION BY THE DROP WEIGHT (VOLUME) METHOD:

1/1

EFFECT OF DROP GROWTH RATE(U) NAVAL RESEARCH LAB

WASHINGTON DC S E PHIPPEN ET AL. 23 MAY 83 NRL-MR-5098


UNCLASSIFIED

F/G 20/4

NL



END
DATE
FILMED
6-83
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

1
2
3

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report 5098	2. GOVT ACCESSION NO. HD-A128409	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) INTERFACIAL TENSION BY THE DROP WEIGHT (VOLUME) METHOD: EFFECT OF DROP GROWTH RATE		5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL problem.
7. AUTHOR(s) S. E. Phippen and R. C. Little		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, D.C. 20375		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Sea Systems Command Washington, D.C. 20362		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61-0097-0-3
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE May 23, 1983
		13. NUMBER OF PAGES 13
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Interfacial tension Surfactant Drop weight method		
20. <input checked="" type="checkbox"/> ABSTRACT (Continue on reverse side if necessary and identify by block number) An investigation has been made of the effect of drop rate growth on the interfacial tension as determined by the drop weight method. A series of surfactant concentrations for two different surfactants — Aerosol OT and Witconate P10-59 — yielded data which allowed a corrective equation to be developed. A		

CONTENTS

I. INTRODUCTION	1
II. EXPERIMENTAL PROCEDURE	2
III. RESULTS AND DISCUSSION	3
IV. RECOMMENDED FUTURE PROJECTS	4
REFERENCES	4



Accession For	
NTIS GSAI	<input checked="checked" type="checkbox"/>
DTIC T-3	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justice	<input type="checkbox"/>
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

INTERFACIAL TENSION BY THE DROP WEIGHT (VOLUME) METHOD:
EFFECT OF DROP GROWTH RATE

I. INTRODUCTION

The drop volume method is considered to be a very accurate and reproducible technique for the measurement of interfacial tension (IFT) between two liquids providing the following conditions are met:

- a) the orifice is sharply cut and of an accurately known radius
- b) the orifice is carefully ground and fully wetted
- c) the drop is made to detach itself as slowly as possible from the orifice (1,2)

Several improvements have already been made on the method; a correction factor has been developed and refined to increase the precision of the interpretation of the data. Lohnstein (3), and Harkins and Humphrey (4) developed a correction factor, $\psi(r/a)$, to account for the difference between the total volume below the orifice and the actual volume of the falling drop. Harkins and Brown (1) later developed a similar correction factor $f(r/v^{1/3})$ (5), which was easier to obtain. Wilkinson (6) derived a fourth power polynomial equation to mathematically convert the correction factor from $f(r/v^{1/3})$ to $\psi(r/a)$ since the latter is considered more accurate (6).

Improvements have also been made in the delivery technique of the dispersed phase to reduce drop distortion caused by fast flow rates. Wilkinson varied the flow rate of the dispersed phase by hand-turning an Agla micrometer syringe. He formed 95% of the drop rapidly (30 seconds), waited at least 60 seconds, then took 30 seconds to slowly turn off the remaining 5% of the drop (6).

Eva Tornberg (2) constructed a unique apparatus to regulate the flow of the dispersed phase. Tornberg forced the dispersed phase through the syringe with a step motor driven by a variable frequency oscillator. The step motor rotated a screw which depressed a piston causing a drop to form at the orifice of a brass tip. An adjustable oscillator pulse rate (1 to 240 Hz) and interchangeable screws regulated the rate of drop formation. Tornberg formed 90% of the drop at 240 Hz and the last 10% of the drop at 10 Hz to reduce the error produced by fast flow rates in the last stages of drop development (2).

Sharma also developed a new apparatus to deliver the dispersed phase at variable flow rates. The apparatus consists of glass and rubber tubing, stopcocks and Herman's clips with screws. The screws in the rubber tubing were adjusted to control

Manuscript approved March 30, 1983.

the flow rate of the dispersed phase through a pipette. The flow rate could be controlled to within ± 0.006 drops/min. (8).

This investigation was conducted in order to study the effect of flow rate (uninterrupted) on the error produced in the calculated interfacial tension value. A correction factor was derived to calculate the true interfacial tension value from data obtained at higher constant flow rates. This study concentrates on low interfacial tension values and moderate flow rates.

II. EXPERIMENTAL PROCEDURE

An Agla Micrometer Syringe Kit, with a metal capillary needle ($r = .0457$ cm) attached to the ground nozzle, was used to determine drop volumes. The volumes were read from a graduated barrel and these were used to determine the interfacial tension values. Flow rates were altered by a four watt motor and pulley system in which a thread was first looped around the micrometer head and then around the motor-driven pulley (see Figure 1.) Four volumetric flow rates were investigated:

volumetric flow rates (cm^3/s):	1.33×10^{-4}	2.98×10^{-4}	6.28×10^{-4}	12.8×10^{-4}
pulley diameter (cm):	1.3	3	6	12.5

All measurements were made at 25°C . The two surfactants studied were Aerosol OT (American Cyanamid) and Witconate P10-59 (Witco Chemical Co.) Methyl salicylate was used for the dispersed phase. The concentration of surfactant in the aqueous phase was varied by diluting the surfactant stock solution with distilled water. Drops were formed in a five ml beaker filled with four ml of surfactant solution. At each volumetric flow rate, the volume of one drop was calculated from the average of ten drops formed successively. After ten successive drops, the beaker was rinsed with distilled water and acetone and refilled with surfactant solution. Again, the volume of one drop was calculated. This procedure was repeated two to four times at each volumetric flow rate. The volumes thus obtained were used in the following equation to calculate an interfacial tension value at each volumetric flow rate.

$$\gamma = \frac{V\Delta\rho gF}{r} \quad [1]$$

where: γ = interfacial tension (dynes/cm)

V = volume of one drop (cm^3)

$\Delta\rho$ = density difference between the continuous and dispersed phase (g/cm^3)

F = correction factor =
 $0.14782 + 0.27896(r/v^{1/3}) - 0.166(r/v^{1/3})^2$

g = gravitation constant

r = capillary radius (cm)

III. RESULTS AND DISCUSSION

To determine the effect of flow rate upon the calculated interfacial tension, graphs were made of interfacial tension vs. volumetric flow rate at selected surfactant concentrations (see Figures 2 and 3). The calculated interfacial tension was found to be a linear function of flow rate at high surfactant concentration and low interfacial tension values. As the interfacial tension increased with decreasing surfactant concentration, the relationship became increasingly curvilinear. An empirical equation was developed to establish a relationship between the calculated interfacial tension and flow rate:

$$\text{or } \gamma_v = b \sqrt{v} + \gamma_0 \quad [2]$$

where: γ_v = calculated interfacial tension (dynes/cm) at the corresponding flow rate

γ_0 = true interfacial tension (dynes/cm) at an infinitely slow rate ($v = 0$)

b = slope of relation

v = volumetric flow rate (cm^3/s)

Figures 2 and 3 illustrate the experimental data obtained.

A least squares plot was made to determine the constant b and true interfacial tension for each surfactant dilution over the range of flow rates allowed by the experimental equipment. The results of this exercise for each surfactant are reported in Tables 1 and 2. The ratios of true (extrapolated) interfacial tension to the b parameter, γ_0/b , were analyzed statistically. It was found that over the range of interfacial tension studied the mean value of γ_0/b was 0.1178 with a standard deviation of 0.0214 and is applicable to both surfactants.

Equation [2] may therefore be rearranged into the form:

$$\frac{\gamma_v - \gamma_0}{\gamma_0} = \frac{b}{\gamma_0} \sqrt{v} \quad [3]$$

after dividing through by γ_0 . Since the existing data suggest that γ_0/b = constant, equation [3] may be rearranged to:

$$\gamma_o = \left(\frac{b'}{b' + \sqrt{v}} \right) \gamma_v \quad [4]$$

$$\text{where } b' = \gamma_o / b = 0.1178$$

or

$$\gamma_o = k_v \gamma_v \quad [5]$$

$$\text{where } k_v = \left(\frac{0.1178}{0.1178 + \sqrt{v}} \right) = \text{correction factor}$$

Using the present drop volume apparatus, an excellent estimate may be made of the true IFT when equation [5] is used to determine the corrective factor k_v . Table 3 illustrates values of γ_o extrapolated at $v = 0$ and values of γ_o calculated using equation [5].

The data collected here, however, are for two surfactants. It is not known how surfactants which may be predisposed to producing strong surface tension aging effects may impact upon the results presented here. However, it is felt that this analysis suggests a meaningful method by which drop formation rates may be accounted for in the determination or estimation of the true interfacial tension.

IV. RECOMMENDED FUTURE PROJECTS

1. This study was conducted using two anionic surfactants: Aerosol OT and Witconate P10-59. It would be useful to repeat the above procedure and calculations for nonionic and cationic surfactants to determine the extent that the corrective procedures presented here for two surfactants applies in the general case.
2. It would be worthwhile to determine what kind of complications develop when a corrective procedure such as this is used in the case of surfactants which produce strong surface aging effects.

REFERENCES

1. Harkins, W. D. and Brown, F. E., J. of Amer. Chem. Soc., 41, 499 (1919).
2. Tornberg, E., J. of Coll. and Interf. Sci., 60, 50 (1977).
3. Lohnstein, T., Ann. Physic, 20(4), 606 (1906).
4. Wilkinson, M. C., J. of Coll. and Interf. Sci., 35, 144 (1971).

5. Harkins, W. D. and Humphrey, E. C., J. of Amer. Chem. Soc., 38, 240 (1916).
6. Wilkinson, M. C., J. of Coll. and Interf. Sci., 40, 14 (1972).
7. Lando, J. L. and Oakley, H. T., J. of Coll. and Interf. Sci., 25, 526-30 (1967).
8. Sharma, R. R., Indian J. Technol., 3, 180-182 (1965).




Figure 1. Diagram of Agla-Micrometer Syringe: 1) 4 watt motor; 2) pulley; 3) thread; 4) micrometer head; 5) graduated barrel 6) metal plunger; 7) glass syringe; 8) metal capillary needle




Figure 2. Plot of Calculated Interfacial Tension vs. Square Root of Volumetric Flow Rate for Aerosol OT Solutions: 1) .70 wt. percent; 2) .27 wt. percent; 3) .24 wt. percent; 4) .1 wt. percent; 5) .063 wt. percent; 6) .053 wt. percent; 7) .047 wt. percent; 8) .037 wt. percent; 9) .021 wt. percent; 10) .007 wt. percent




Figure 3. Plot of Calculated Interfacial Tension vs. Square Root of Volumetric Flow Rate for Witconate P10-59 Solutions: 1) .17 wt. percent; 2) .14 wt. percent; 3) .13 wt. percent; 4) .11 wt. percent; 5) .08 wt. percent; 6) .06 wt. percent; 7) .058 wt. percent; 8) .046 wt. percent; 9) .036 wt. percent; 10) .028 wt. percent; 11) .023 wt. percent; 12) .014 wt. percent.

Table 1. Analysis of Aerosol OT Interfacial Tension Data

Conc. Wt. %	\sqrt{v} (cm ³ /s)	IFT (dynes/cm)	b	IFT ₀ (dynes/cm)	Correl.
0.007	1.16x10 ⁻²	14.6	109	13.7	0.978
	1.73x10 ⁻²	15.8			
	2.51x10 ⁻²	16.5			
	3.58x10 ⁻²	17.4			
0.021	same	10.9	102	9.94	0.981
	as	11.8			
	above	12.7			
		13.4			
0.037	same	9.11	67.5	8.22	0.99
	as	9.27			
	above	9.87			
		10.7			
0.047	same	7.04	62.9	6.38	0.983
	as	7.63			
	above	8.23			
		8.71			
0.053	same	5.96	80.2	5.10	0.997
	as	6.56			
	above	7.15			
		7.94			
0.063	same	5.63	56.9	5.14	0.947
	as	6.20			
	above	6.82			
		7.02			
0.100	same	4.04	36.4	3.73	0.961
	as	4.47			
	above	4.73			
		4.94			
0.240	same	2.28	16.1	2.11	0.989
	as	2.42			
	above	2.49			
		2.69			
0.270	same	1.99	14.9	1.89	0.927
	as	2.21			
	above	2.30			
		2.38			
0.700	same	1.16	7.98	1.10	0.947
	as	1.27			
	above	1.31			
		1.37			

Table 2. Analysis of Witconate P10-59 Interfacial Tension Data

Conc. Wt. %	\sqrt{v} (cm ³ /s)	IFT (dynes/cm)	b	IFT ₀ (dynes/cm)	Correl.
0.014	1.16x10 ⁻²	11.3	92.4	10.5	0.967
	1.73x10 ⁻²	12.3			
	2.51x10 ⁻²	13.1			
	3.58x10 ⁻²	13.7			
0.023	same	10.3	70.9	9.60	0.979
	as	11.0			
	above	11.5			
		12.0			
0.028	same	9.31	71.2	8.71	0.962
	as	10.1			
	above	10.6			
		11.1			
0.036	same	8.59	60.1	8.02	0.983
	as	9.16			
	above	9.62			
		10.1			
0.046	same	7.58	42.0	7.18	0.979
	as	7.97			
	above	8.33			
		8.62			
0.058	same	6.23	43.4	5.74	0.985
	as	6.43			
	above	6.94			
		7.24			
0.060	same	5.68	58.2	5.10	0.989
	as	6.23			
	above	6.51			
		7.17			
0.080	same	4.17	31.0	3.85	0.994
	as	4.40			
	above	4.66			
		4.93			
0.110	same	3.31	26.9	3.05	0.984
	as	3.56			
	above	3.77			
		3.98			
0.130	same	3.12	23.4	2.92	0.953
	as	3.43			
	above	3.46			
		3.75			

Table 2 (continued)

Conc. Wt. %	\sqrt{v} (cm ³ /s)	IFT (dynes/cm)	b	IFT ₀ (dynes/cm)	Correl.
0.140	1.16x10 ⁻²	2.99	22.3	2.76	0.994
	1.73x10 ⁻²	3.18			
	2.51x10 ⁻²	3.32			
	3.58x10 ⁻²	3.55			
0.170	same	2.69	19.5	2.48	0.998
	as	2.83			
	above	2.97			
		3.17			

Table 3. Extrapolated IFT and Calculated IFT (Equation [5])

\sqrt{v} (cm ³ /s)	γ_v (dynes/cm)	k_v	$\gamma_o(1)$ (dynes/cm)	$\gamma_o(2)$ (dynes/cm)
1.16x10 ⁻²	1.16	0.911	1.10	1.06
1.73x10 ⁻²	1.27	0.872	same	1.11
2.51x10 ⁻²	1.31	0.824	same	1.08
3.58x10 ⁻²	1.37	0.767	same	1.05
same	9.31	0.911	8.71	8.47
as	10.1	0.872	same	8.85
above	10.6	0.824	same	8.78
	11.1	0.767	same	8.53
same	14.6	0.911	13.7	13.3
as	15.8	0.872	same	13.7
above	6.5	0.824	same	13.6
	17.4	0.767	same	13.3

(1) Extrapolated value ($v = 0$) of IFT

(2) Calculated value of IFT from Equation [5]

**DAT
FILM**